

Elkay WaterSentry Replacement Filter (Bottle Fillers & Liv Pro) Model(s) 51300C

PRODUCT SPECIFICATIONS

Elkay WaterSentry Replacement Filter (Bottle Fillers & Liv Pro). Overall dimensions are 3-1/8" x 3-1/8" x 9-1/2".

| Special Features: | Filtered |
|------------------------|--------------------------|
| Dimensions: | 3-1/8" x 3-1/8" x 9-1/2" |
| Shipping Weight: | 2 lbs. |
| Flow Rate: | 1.5 GPM (5.6 L/m) |
| Capacity: | 3000 gal. (11356 L) |
| Temperature: | 40-100°F (4-38°C) |
| Initial Pressure Drop: | 2-5 PSI (14-34 kPa) |
| Maximum Pressure: | 105 PSI (724 kPa) |
| Minimum Pressure: | 20 PSI (138 kPa) |
| Water Inlet: | 3/8" (9.5mm) O.D. tube |
| Water Outlet: | 1/4" (6.4mm) O.D. tube |

Special Note: Please note, some Elkay filters will ship with a clear cap, instead of a red cap. While colors of filter caps may vary based on inventory levels, there is no effect on filter performance.

- Replacement filter for models with WaterSentry filtration system (Bottle Fillers & Liv Pro).
- Filter should be replaced every 3,000 gallons (expires 1 year after installation).
- Equipped with quick-disconnect, 1/4-turn installation, as well as automatic inlet shut-off valve that closes when filter is removed.
- Designed to reduce lead, particles and chlorine. Also reduces odors and discoloration from incoming water.
- Spun polypropylene prefilter mesh to prevent large, coarse sediment and particles from entering and clogging filter media.
- Filter is tested and certified to NSF 42 and 53 for lead, Class 1 particulate, chlorine taste and odor reduction.



Included with Product:

3000 gallon replacement filter cartridge

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.


Product Compliance:

NSF 372 (lead free) NSF 42 NSF 53



Installation Instructions (PDF) - 98526C





| PART: | QTY: |
|-----------|------|
| PROJECT: | |
| CONTACT: | |
| DATE: | |
| NOTES: | |
| APPROVAL: | |

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.